Strands Siberia DR LED light-bar, E-approved

Strands double-rowed LED light-bar with dual colour position-light in the middle. Standard and XPA series. E-approved for road use.






E-approved LED bars by Strands with dual-colour position-light in the middle making it a stylish and modern look. The LED bars are available in various lengths.

Standard :
12" version: 8.000 theoretical lumen - 1 Lux @ 437meter
22" version: 16.000 theoretical lumen - 1 Lux @ 450meter

The XPA version has a lower reference number, but shines significantly longer/wider than standard in Xperience Mode:
8" version: 4.350 theoretical lumen - 1 Lux @ 544meter
12" version: 6.757 theoretical lumen - 1 Lux @ 529meter
22" version: 13.514 theoretical lumen - 1 Lux @ 767meter
32" version: 20.271 theoretical lumen - 1 Lux @ 942meter
42" version: 27.028 theoretical lumen - 1 Lux @ 1.110meter

The dual-color position-light gives you the possibility to change between white and yellow positions-light as you feel like it so that it fits your vehicle.

The combo-light takes the best of a "spot-" and "flood" light bar. On each side, there are flood lenses, and in the center, spot lenses. This way you have a good combination of the broad light spreading from the sides and the focused light in the center.

The lens glass is produced in polycarbonate and the lamp housing is made of powder-coated aluminum to achieve a sleek design and good cooling for the LEDs.

There are brackets included for mounting and also a pre-mounted 4-pin DT plug, which makes the installation much easier.

- Black: Minus / -
- Red: High-beam
- White: White position-light
- Yellow: Yellow position-light

E-approvements: ECE R112, R7, R10, CE
XPA : ECe R10.06 R148 R149


Ref.: 809179, 809180, 809181, 809182, 809183
XPA Ref. 809425A, 809426A, 809427A, 809428A, 809429A

Buy online at:


www.matronics.eu/24607011




DR 12" - OUTLET
SKU 24607011
LEDs: 20
Voltage: 10-40V DC
Consumption: 45W
Lumen theoretical: 8000lm
Lumen effective: 3294lm
Reference: 45
Kelvin: 6000K
Operating temperature: – 30°C to +65°C
Dimensions: 71,6 x 76 x 307mm




XPA DR 8"
SKU 24607010A
Voltage: 10-32V DC
Consumption: 55W
Lumen theoretical: 4800lm
Lumen effective: 4300lm
Reference: 20
Kelvin: 5700K
Operating temperature: – 35°C to +60°C




XPA DR 12"
SKU 24607011A
Voltage: 10-32V DC
Consumption: 84W
Lumen theoretical: 6757lm
Lumen effective: 6120lm
Reference: 20
Kelvin: 5700K
Operating temperature: – 30°C to +60°C



XPA DR 22"
SKU 24607012A
Voltage: 10-32V DC
Consumption: 149W
Lumen theoretical: 13514lm
Lumen effective: 11500lm
Reference: 20
Kelvin: 5700K
Operating temperature: – 35°C to +60°C



XPA DR 32"
SKU 24607013A
Voltage: 10-32V DC
Consumption: 245W
Lumen theoretical: 20271lm
Lumen effective: 19150lm
Reference: 20
Kelvin: 5700K
Operating temperature: – 35°C to +60°C



XPA DR 42"
SKU 24607014A
Voltage: 10-32V DC
Consumption: 400W
Lumen theoretical: 27028lm
Lumen effective: 2550lm
Reference: 20
Kelvin: 5700K
Operating temperature: – 30°C to +60°C

Product pictures







