DIOSPOT OPTI GU10 Downlight for insulation - Swivel - restsalg 394

Discontinued item 3 pcs left

Note that this product is a clearance sale. We only have 3 products(s) in stock.

OUTLET !! - LIMITED STOCK

Downlight in the DIOSPOT OPTI series is a downlight for indoor use, that is approved for mounting in insulation and flammable materials. They are easily installed with Torx 10 screw system. The front ring is with a double feather function, which makes sure, that it fits tight to the sealing, regardless of the type.

The downlight is available in brushed steel, white, black, and brass. They are all adjustable/tiltable at a 25-degree angle so that you can adjust them for your needs. Approved for use in areas 1 and 2 in rooms with bath or shower.

The downlight has a big connection box with a 5-pole terminal block, where you have the opportunity to route cables. Furthermore, there are unique mounting flaps, that make sure that you get a safe installation in all types of sealings from 4mm to 36mm.

The downlight is WITHOUT light-source.

Facts for Black
Cutout hole: Ø75mm
Diameter: Ø87mm
Installation height: Ø63mm
Max consumption, LED: 7W
socket: GU10
Swivel: 25 degrees
Warranty: 5 years
IP rating
Rating: IP 44
Solid: 4 - Protected < 1mm
Liquid: 4 - Water splash, all directions
Pick
Brushed steel
Black

Buy online at:

www.matronics.eu/970000



DIOSPOT OPTI GU10 Downlight for insulation - Swivel - restsalg 394

SKU 970000