Cable, LIW 100m spool

Single wire for connections inside machines, enclosures and similar. 0.25mm2, 0.5mm2 and 1.5mm2 in 8 different colors






PVC single-core wire with for connections inside machines, enclosures and similar.

The wires are available as 0.25mm2, 0.5mm2 and 1.5mm2 in 8 different colors

Max peak voltage of 900V, and flexible operating temperature from -5 to 70 degrees, and fixed installation temperature from -30 to 80 degrees. This allows you to use this cable for any typical purpose.

The wires conform to the Low-Voltage Directive 2006/95/EG

Buy online at:

www.matronics.eu/509105-BK

Specifications

Sheath	PVC
Operating temperature, fixed	-30 to 80 degrees
Operating temperature, fleksibel	-5 to 70 degrees
Max peak voltage	900V



0.25mm2, Black
SKU 509105-BK



0.25mm2, Blue
SKU 509105-BL



0.25mm2, Brown
SKU 509105-BR



0.25mm2, Green
SKU 509105-GR



0.25mm2, Gray
SKU 509105-GY



0.25mm2, Red
SKU 509105-RD



0.25mm2, Yellow
SKU 509105-YL



0.25mm2, White
SKU 509105-WH



0.5mm2, Black
SKU 509110-BK



0.5mm2, Blue
SKU 509110-BL



0.5mm2, Brown
SKU 509110-BR



0.5mm2, Green
SKU 509110-GR



0.5mm2, Gray
SKU 509110-GY



0.5mm2, Red
SKU 509110-RD



0.5mm2, White
SKU 509110-WH



0.5mm2, Yellow
SKU 509110-YL



1.5mm2, Black
SKU 509115-BK



1.5mm2, Blue
SKU 509115-BL



1.5mm2, Brown
SKU 509115-BR



1.5mm2, Gray
SKU 509115-GY



1.5mm2, Red
SKU 509115-RD



1.5mm2, White
SKU 509115-WH



1.5mm2, Yellow
SKU 509115-YL



1.5mm2, Green
SKU 509115-GR

Product pictures







